

Safety Data Sheet

400-1 SUPREME LUBRICANT

SDS Revision Date:

08/22/2017

1. Identification

1.1. Product identifier

Product Identity

400-1 SUPREME LUBRICANT

Alternate Names

400-1 SUPREME LUBRICANT, Petroleum Grease

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use

See Technical Data Sheet.

Application Method

See Technical Data Sheet.

1.3. Details of the supplier of the safety data sheet

Company Name

Steelco Industrial Lubricants, Inc.
PO BOX 136,
VALPARATSO, IN 46384

Emergency

24 hour Emergency Telephone No.

(219) 462-0333

Customer Service: Steelco Industrial Lubricants, Inc.

(219) 462-0333

2. Hazard(s) identification

2.1. Classification of the substance or mixture

Acute Tox. 4;H332

Harmful if inhaled.

Skin Irrit. 3;H316

Causes mild skin irritation. (Not adopted by US OSHA)

Eye Irrit. 2;H319

Causes serious eye irritation.

Skin Sens. 1;H317

May cause an allergic skin reaction.

Resp. Sens. 1;H334

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

STOT SE 3;H335

May cause respiratory irritation.

STOT RE 1;H372

Causes damage to organs through prolonged or repeated exposure. Specific Target Organs: (lungs)

2.2. Label elements



Danger

H316 Causes mild skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

Safety Data Sheet

400-1 SUPREME LUBRICANT

SDS Revision Date:

08/22/2017

H334 May cause allergic or asthmatic symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation.

H372 Causes damage to organs through prolonged or repeated exposure.

[Prevention]:

P261 Avoid breathing dust / fume / gas / mist / vapors / spray.

P264 Wash thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves / eye protection / face protection.

[Response]:

P302+352 IF ON SKIN: Wash with plenty of soap and water.

P304+312 IF INHALED: Call a POISON CENTER or doctor / physician if you feel unwell.

P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing.

P314 Get Medical advice / attention if you feel unwell.

P321 Specific treatment (see information on this label).

P333+313 If skin irritation or a rash occurs: Get medical advice / attention.

P337+313 If eye irritation persists: Get medical advice / attention.

P341 If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.

P342+311 If experiencing respiratory symptoms: Call a POISON CENTER or doctor / physician.

P363 Wash contaminated clothing before reuse.

[Storage]:

P403+233 Store in a well ventilated place. Keep container tightly closed.

P405 Store locked up.

[Disposal]:

P501 Dispose of contents / container in accordance with local / national regulations.

3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Residual oils (petroleum), solvent-refined; Baseoil- unspecified CAS Number: 0064742-01-4	50 - 75	Eye Irrit. 2;H319 Skin Irrit. 3;H316 STOT SE 3;H335	[1]
Distillates (petroleum), solvent refined heavy paraffinic CAS Number: 0064741-88-4	25 - 50	Not Classified	[1]
Cristobalite CAS Number: 0014464-46-1	1 - 5	STOT RE 1;H372	[1]
Crystalline silica (Quartz) (non respirable)	1 - 5	Not Classified	[1][2]

Safety Data Sheet

400-1 SUPREME LUBRICANT

SDS Revision Date:

08/22/2017

CAS Number: 0014808-60-7			
Distillate (petroleum) hydrotreated heavy naphthenic CAS Number: 0064742-52-5	1 - 5	Asp. Tox. 1;H304	[1]
MOLYBDENUM, BIS(DIBUTYLCARBAMODITHIOATO)DI-MU.-OX CAS Number: 0068412-26-0	1 - 5	Acute Tox. 2;H330	[1]
Acetone CAS Number: 0000067-64-1	1 - 5	Flam. Liq. 2;H225 Eye Irrit. 2;H319 STOT SE 3;H336	[1][2]
Polybutene CAS Number: 0009003-29-6	1 - 5	Not Classified	[1]
Polyisoprene latex CAS Number: 0009006-04-6	0.10 - 1.0	Resp. Sens. 1;H334 Skin Sens. 1;H317	[1]

In accordance with paragraph (i) of §1910.1200, the specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

[1] Substance classified with a health or environmental hazard.

[2] Substance with a workplace exposure limit.

[3] PBT-substance or vPvB-substance.

*The full texts of the phrases are shown in Section 16.

Section 4. First aid measures

4.1. Description of first aid measures

General

In all cases of doubt, or when symptoms persist, seek medical attention.
Never give anything by mouth to an unconscious person.

Inhalation

Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give artificial respiration. If unconscious, place in the recovery position and obtain immediate medical attention. Give nothing by mouth.

Eyes

Irrigate copiously with clean water for at least 15 minutes, holding the eyelids apart and seek medical attention.

Skin

Remove contaminated clothing. Wash skin thoroughly with soap and water or use a recognized skin cleanser.

Ingestion

If swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

Overview

EYE: May cause irritation.
SKIN: May cause irritation or dermatitis. Prolonged exposure may cause gastrointestinal disturbances.
INHALATION: Not expected to be a problem.
INGESTION: Prolonged exposure may cause nausea, vomiting and/or diarrhea.
Medical Conditions Aggravated By Exposure: Treat symptomatically.
Treat symptomatically. See section 2 for further details.

Inhalation

Harmful if inhaled. May cause respiratory irritation. May cause allergy or asthma symptoms of breathing difficulties if inhaled.

Eyes

Causes serious eye irritation.

Skin

May cause an allergic skin reaction. Causes mild skin irritation.

Safety Data Sheet

400-1 SUPREME LUBRICANT

SDS Revision Date:

08/22/2017

Section 5. Fire-fighting measures

5.1. Extinguishing media

Dry chemical, carbon dioxide, foam or water.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition: Carbon dioxide and carbon monoxide may form when heated to decomposition

Avoid breathing dust / fume / gas / mist / vapors / spray.

5.3. Advice for fire-fighters

Use water to cool fire exposed containers, structures and to protect personnel, water or foam may cause frothing. Fire Fighters may need to wear positive supplied breathing apparatus.

ERG Guide No. ---

Section 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Put on appropriate personal protective equipment (see section 8).

6.2. Environmental precautions

Do not allow spills to enter drains or waterways.

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

6.3. Methods and material for containment and cleaning up

Absorb with fire resistant absorbent, shovel up & dispose of at an appropriate disposal facility in accordance with current local, state & federal laws and regulations.

Section 7. Handling and storage

7.1. Precautions for safe handling

Handle containers carefully to prevent damage and spillage.

Do Not wear oil soaked clothing. Wash after handling.

See section 2 for further details. - [Prevention]:

7.2. Conditions for safe storage, including any incompatibilities

Incompatible materials: High O₂, content, chlorines and gases.

See section 2 for further details. - [Storage]:

7.3. Specific end use(s)

No data available.

Section 8. Exposure controls and personal protection

Safety Data Sheet

400-1 SUPREME LUBRICANT

SDS Revision Date:

08/22/2017

8.1. Control parameters

Exposure			
CAS No.	Ingredient	Source	Value
0000067-64-1	Acetone	OSHA	TWA 1000 ppm (2400 mg/m ³) STEL 2400 mg/m ³
		ACGIH	TWA: 500 ppm STEL: 750 ppm
		NIOSH	250 ppm (590 mg/m ³) TWA
		Supplier	No Established Limit
0009003-29-6	Polybutene	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
0009006-04-6	Polyisoprene latex	OSHA	No Established Limit
		ACGIH	TWA: 0.001 mg/m ³ Skin, S Revised 2004; 2008; 2010,
		NIOSH	No Established Limit
		Supplier	No Established Limit
0014464-46-1	Cristobalite	OSHA	No Established Limit
		ACGIH	TWA: 0.025 mg/m ³
		NIOSH	No Established Limit
		Supplier	No Established Limit
0014808-60-7	Crystalline silica (Quartz) (non respirable)	OSHA	PEL 50 µg/m ³
		ACGIH	TWA: 0.025 mg/m ³ A1, 1
		NIOSH	0.05 mg/m ³ TWA (respirable)
		Supplier	No Established Limit
0064741-88-4	Distillates (petroleum), solvent refined heavy paraffinic	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
0064742-01-4	Residual oils (petroleum), solvent-refined; Baseoil-unspecified	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
0064742-52-5	Distillate (petroleum) hydrotreated heavy naphthenic	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
0068412-26-0	MOLYBDENUM, BIS(DIBUTYLCARBAMODITHIOATO)DI-MU.-OX	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit

Contains mineral oil. The exposure limits for oil mist are 5 mg/m³ OSHA PEL and 10 mg/m³ ACGIH.

Safety Data Sheet

400-1 SUPREME LUBRICANT

SDS Revision Date:

08/22/2017

8.2. Exposure controls

Respiratory	If workers are exposed to concentrations above the exposure limit they must use the appropriate, certified respirators.
Eyes	Protective safety glasses recommended
Skin	Protective (oil resistant) gloves recommended. Oil resistant apron.
Engineering Controls	Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapor below occupational exposure limits suitable respiratory protection must be worn.
Other Work Practices	Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

See section 2 for further details.

Section 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Dark Orange Grease
Odor	petroleum odor
Odor threshold	Not determined
pH	Not Measured
Melting point / freezing point	Not Measured
Initial boiling point and boiling range	Not Measured
Flash Point	545F, Base Oil C.O.C
Evaporation rate (Ether = 1)	Butyl Acetate 0.01
Flammability (solid, gas)	Not Applicable
Upper/lower flammability or explosive limits	Lower Explosive Limit: Not Measured Upper Explosive Limit: Not Measured
Vapor pressure (Pa)	(mm Hg): 0.01
Vapor Density	(Air=1): 12.0
Specific Gravity	(H2O=1): 0.8
Solubility in Water	Insoluble
Partition coefficient n-octanol/water (Log Kow)	Not Measured
Auto-ignition temperature	Not Measured
Decomposition temperature	Not Measured
Viscosity (cSt)	Not Measured

9.2. Other information

DMSO extract by IP346: Less than 3.0 wt % (mineral oil component only)

Section 10. Stability and reactivity

Safety Data Sheet

400-1 SUPREME LUBRICANT

SDS Revision Date:

08/22/2017

10.1. Reactivity

Hazardous Polymerization will not occur.

10.2. Chemical stability

Stable under normal circumstances.

10.3. Possibility of hazardous reactions

No data available.

10.4. Conditions to avoid

High O₂, content, chlorines and gases.

10.5. Incompatible materials

High O₂, content, chlorines and gases.

10.6. Hazardous decomposition products

Carbon dioxide and carbon monoxide may form when heated to decomposition

Section 11. Toxicological information

Acute toxicity

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LC50, mg/L/4hr	Inhalation Dust/Mist LC50, mg/L/4hr	Inhalation Gas LC50, ppm
Residual oils (petroleum), solvent-refined; Baseoil- unspecified - (64742-01-4)	No data available	No data available	No data available	No data available	No data available
Distillates (petroleum), solvent refined heavy paraffinic - (64741-88-4)	> 5,000.00, Rat - Category: NA	> 5,000.00, Rabbit - Category: NA	No data available	11.00, Rat - Category: NA	No data available
Cristobalite - (14464-46-1)	No data available	No data available	No data available	No data available	No data available
Crystalline silica (Quartz) (non respirable) - (14808-60-7)	No data available	No data available	No data available	No data available	No data available
Distillate (petroleum) hydrotreated heavy naphthenic - (64742-52-5)	> 5,000.00, Rat - Category: NA	No data available	No data available	5.70, Rat - Category: NA	No data available
MOLYBDENUM, BIS(DIBUTYLCARBAMODITHIOATO)DI-MU.-OX - (68412-26-0)	No data available	No data available	No data available	No data available	No data available
Acetone - (67-64-1)	5,800.00, Rat - Category: NA	7,426.00, Guinea Pig - Category: NA	76.00, Rat - Category: NA	50.10, Rat - Category: NA	No data available
Polybutene - (9003-29-6)	No data available	No data available	No data available	No data available	No data available
Polyisoprene latex - (9006-04-6)	No data available	No data available	No data available	No data available	No data available

Carcinogen Data

Safety Data Sheet

400-1 SUPREME LUBRICANT

SDS Revision Date:

08/22/2017

CAS No.	Ingredient	Source	Value
0000067-64-1	Acetone	OSHA	Regulated Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0009003-29-6	Polybutene	OSHA	Regulated Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0009006-04-6	Polyisoprene latex	OSHA	Regulated Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0014464-46-1	Cristobalite	OSHA	Regulated Carcinogen: No
		NTP	Known: Yes; Suspected: No
		IARC	Group 1: Yes; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0014808-60-7	Crystalline silica (Quartz) (non respirable)	OSHA	Regulated Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0064741-88-4	Distillates (petroleum), solvent refined heavy paraffinic	OSHA	Regulated Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0064742-01-4	Residual oils (petroleum), solvent-refined; Baseoil-unspecified	OSHA	Regulated Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0064742-52-5	Distillate (petroleum) hydrotreated heavy naphthenic	OSHA	Regulated Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0068412-26-0	MOLYBDENUM, BIS(DIBUTYLCARBAMODITHIOATO)DI-MU.-OX	OSHA	Regulated Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;

Classification	Category	Hazard Description
Acute toxicity (oral)	---	Not Applicable
Acute toxicity (dermal)	---	Not Applicable
Acute toxicity (inhalation)	4	Harmful if inhaled.
Skin corrosion/irritation	3	Causes mild skin irritation. (Not adopted by US OSHA)
Serious eye damage/irritation	2	Causes serious eye irritation.

Safety Data Sheet

400-1 SUPREME LUBRICANT

SDS Revision Date:

08/22/2017

Respiratory sensitization	1	May cause allergy or asthma symptoms of breathing difficulties if inhaled.
Skin sensitization	1	May cause an allergic skin reaction.
Germ cell mutagenicity	---	Not Applicable
Carcinogenicity	---	Not Applicable
Reproductive toxicity	---	Not Applicable
STOT-single exposure	3	May cause respiratory irritation.
STOT-repeated exposure	1	Causes damage to organs through prolonged or repeated exposure.
Aspiration hazard	---	Not Applicable

Section 12. Ecological information

12.1. Toxicity

No additional information provided for this product. See Section 3 for chemical specific data.

Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/l	48 hr EC50 crustacea, mg/l	ErC50 algae, mg/l
Residual oils (petroleum), solvent-refined; Baseoil-unspecified - (64742-01-4)	Not Available	Not Available	Not Available
Distillates (petroleum), solvent refined heavy paraffinic - (64741-88-4)	Not Available	Not Available	Not Available
Cristobalite - (14464-46-1)	Not Available	Not Available	Not Available
Crystalline silica (Quartz) (non respirable) - (14808-60-7)	Not Available	Not Available	Not Available
Distillate (petroleum) hydrotreated heavy naphthenic - (64742-52-5)	5,000.00, Oncorhynchus mykiss	1,000.00, Daphnia magna	1,000.00 (96 hr), Scenedesmus subspicatus
MOLYBDENUM, BIS(DIBUTYLCARBAMODITHIOATO)DI-.MU.-OX - (68412-26-0)	Not Available	Not Available	Not Available
Acetone - (67-64-1)	100.00, Pimephales promelas	10.00, Daphnia magna	20.565 (72 hr), Ulva pertusa
Polybutene - (9003-29-6)	Not Available	Not Available	Not Available
Polyisoprene latex - (9006-04-6)	Not Available	Not Available	Not Available

12.2. Persistence and degradability

There is no data available on the preparation itself.

12.3. Bioaccumulative potential

Not Measured

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

Safety Data Sheet

400-1 SUPREME LUBRICANT

SDS Revision Date:

08/22/2017

12.6. Other adverse effects

No data available.

Section 13. Disposal considerations

13.1. Waste treatment methods

Observe all federal, state and local regulations when disposing of this substance.

Section 14. Transport information

	DOT (Domestic Surface Transportation)	IMO / IMDG (Ocean Transportation)	ICAO/IATA
14.1. UN number	Not Applicable	Not Regulated	Not Regulated
14.2. UN proper shipping name	Not Regulated	Not Regulated	Not Regulated
14.3. Transport hazard class(es)	DOT Hazard Class: Not Applicable	IMDG: Not Applicable Sub Class: Not Applicable	Air Class: Not Applicable
14.4. Packing group	Not Applicable	Not Applicable	Not Applicable
14.5. Environmental hazards			
IMDG	Marine Pollutant: No;		
14.6. Special precautions for user	No further information		

Section 15. Regulatory information

Regulatory Overview	The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented.
Toxic Substance Control Act (TSCA)	All components of this material are either listed or exempt from listing on the TSCA Inventory.
WHMIS 1988 Classification	D2A
US EPA Tier II Hazards	Fire: No Sudden Release of Pressure: No Reactive: No Immediate (Acute): Yes Delayed (Chronic): Yes
EPCRA 302 Extremely Hazardous:	
To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.	
EPCRA 313 Toxic Chemicals:	
Cristobalite	

Safety Data Sheet

400-1 SUPREME LUBRICANT

SDS Revision Date:

08/22/2017

Crystalline silica (Quartz) (non respirable)

Proposition 65 - Carcinogens (>0.0%):

Ethyl Benzene

Proposition 65 - Developmental Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Female Repro Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Male Repro Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Section 16. Other information

SDS Revision Date 08/22/2017

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H225 Highly flammable liquid and vapor.

H304 May be fatal if swallowed and enters airways.

H316 Causes mild skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H330 Fatal if inhaled.

H334 May cause allergic or asthmatic symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness and dizziness.

H372 Causes damage to organs through prolonged or repeated exposure.

IMPORTANT NOTE: This information is furnished without warranty, expressed or implied, as to accuracy or completeness. The information is obtained from various sources including the manufacturer and other third party sources. The information may not be valid under all conditions nor if this material is used in combination with other materials or any process. Final determination of suitability of any material is the sole responsibility of the user.

End of Document